

CONTAINER



Dry / Steel		Door openings (mm)		Internal dimensions (mm)			Weight (kg)			Volume (m ³)
Type	Size	Width	Height	Length	Width	Height to load line	Max. Gross	Tare	Max. Payload	
20" std	20' x 8' x 8' 6"	2,340	2,274	5,896	2,350	2,385	27,000	2,150	24,850	33
40" std	40' x 8' x 8' 6"	2,339	2,274	12,035	2,350	2,393	32,500	3,700	28,800	67
40" high	40' x 8' x 9' 6"	2,340	2,577	12,035	2,350	2,697	34,000	3,800	30,200	76
45" high	45' x 8' x 9' 6"	2,340	2,585	13,556	2,352	2,697	32,500	4,800	27,820	86

Dry / Aluminium		Door openings (mm)		Internal dimensions (mm)			Weight (kg)			Volume (m ³)
Type	Size	Width	Height	Length	Width	Height to load line	Max. Gross	Tare	Max. Payload	
40" wide door	40' x 8' x 8' 6"	2,343	2,278	12,056	2,347	2,379	32,500	2,790	29,710	67
40" high	40' x 8' x 9' 6"	2,343	2,584	12,056	2,347	2,684	32,500	2,900	29,600	76
45" high	45' x 8' x 9' 6"	2,340	2,584	13,582	2,347	2,696	32,500	3,900	28,600	86

Flat rack / Steel		Internal dimensions (mm)						Weight (kg)		
Type	Size	Length	Width	Height	Length between headers	Length between corner posts	Width between corner posts	Gross	Tare. Payload	Max. payload
20' fixed-corner	20' x 8' x 8' 6"	5,935	2,398	2,327	5,935	5,693	2,106	24,000	2,560	21,440
20' collapsible	20' x 8' x 8' 6"	5,966	2,418	2,286	5,850	5,422	2,058	30,480	2,970	27,510
40' fixed-corner	40' x 8' x 8' 6"	12,080	2,438	2,103	12,080	11,796	2,114	30,480	5,480	25,000
40' open-end	40' x 8' x 9' 6"	12,192	2,230	1,986	11,900	11,710	2,178	45,000	4,500	40,500
40' flush-fold	40' x 8' x 9' 6"	12,178	2,365	1,943	12,058	11,662	2,224	45,000	5,200	39,800

Flat rack / Steel		Internal dimensions (mm)		Maximum load (kg)		Weight (kg)		
Type	Size	Length	Width	Concentrated (kg/sq.feet)	on mid 10 ft	Max. gross	Tare	Max. payload
40' atd	40' x 8' x 20' 3/8"	12,052	2,438	4,535	12,148	44,440	4,860	39,580

CONTAINER



Open-tops / Steel		Internal dimensions (mm)			Door opening (mm)		Top opening (mm)		Weight (kg)			Volume (m ³)
Type	Size	Length	Width	Height	Width	Height	Length	Width	Max. Gross	Tare	Max. Payload	Capacity
20' open-top	20'x 8'x 8' 6"	5,919	2,340	2,286	2,286	2,251	5,425	2,223	24,000	2,177	28,230	32
40' open-top	40'x 8'x 8' 6"	12,043	2,338	2,272	2,289	2,253	11,622	2,162	30,480	4,300	28,700	64

Open-tops / Aluminium		Internal dimensions (mm)			Door opening (mm)		Top opening (mm)		Weight (kg)			Volume (m ³)
Type	Size	Length	Width	Height	Width	Height	Length	Width	Max. Gross	Tare	Max. Payload	Capacity
20' open-top	20'x 8'x 8' 6"	5,893	2,346	2,353	2,338	2,273	5,488	2,230	30,480	2,250	21,823	32
40' open-top	40'x 8'x 9' 6"	12,029	2,348	2,359	2,338	2,275	11,622	2,188	32,500	3,800	26,180	66